

TECHNICAL DATASHEET

STEP Parquet Primer Warm #6130



Applications:

Water borne insulating primer. Gives a lightly warm radiation on untreated wood. For a lightly natural aspect use STEP Parquet Primer Natural, or for a truly untreated look use SKYLT. Suitable for untreated wood. Does not turn yellow and reduces seam sticking. Always make a test sample on unknown surfaces. Choose STEP Kambala Primer for wood species with saline content like Kambala, Afzelia or Basralocus. Read our user instructions STEP for comprehensive instructions and legend of used symbols. For specific questions, do not hesitate to call us, or app at 0031 6 47057824.

The figures in the scheme below are valid for the fresh product. Circumstances for drying are standardized at 20°C, 65% RAH and sufficient ventilation.

Colour	Pale white liquid, dries transparent and clear. Doesn't yellow.
Odour	Mild
Solids	34 VOL %
pH	8
Viscosity/fluidity	Thin liquid
Sanding	Good
Yield	8 - 10 m ² per litre
Dust dry	1 hour
Next coat	2 - 3 hours

Available in:

1 litre bottle, art. nr. 5260433; EAN 8716544037885 (Box 12 x 1 litre)

4 litre can, art.nr. 5260439; EAN 8716544037892 (Box = 4 x 4 litre)

See SAFETY DATASHEET for a safe and healthful job.